

Material Safety Data Sheet

1. Product and Company Identification

Product name MDF Panel Doors

MSDS Number 0007

Synonyms Ovation, Bravo

Product use Various Construction Uses

Manufacturer Doormerica Products (ABS – Manufacturing)

Sacramento, CA Division 8360 Elder Creek Road. Sacramento, CA 95828-1705

Stockton, CA Division 1488 Tillie Lewis Drive Stockton, CA 95206

Atlanta, GA Division

4475 South Fulton Parkway - Bldg 6 - Suite 200

Union City, GA 30349

Print date May 1, 2010

Telephone Emergency Phone (916) 503-4100

Sacramento, CA (916) 503-4100 Stockton, CA (209) 941-8852 Atlanta, GA (404) 935-4060

2. Hazards Identification

Form Doors are comprised mostly of Wood, MDF and resin based

adhesives.

Odor Color and Odor are dependent on wood species used, but very slight

and aromatic.

OSHA/HCS status While this material is not considered hazardous by the OSHA Hazard

Communication Standard (29 CFR 1910.1200), this MSDS contains valuable information critical to the safe handling and proper use of the product. This MSDS should be retained and available for employees

and other users of this product.

Emergency overview If this product is cut, sanded or manipulated so that dust or airborn

particles may be produced it may become a health hazard.

Potential acute health effects

Inhalation Can cause irritation of the respiratory system.

Ingestion Not likely, can be harmful or fatal.

Skin Handling doors without gloves may lead to wood splinters and or cuts.

Some woods are known to cause allergic skin reactions.

Eyes May cause eye irritation or damage.

Potential chronic health effects

Chronic effects Inhalation exposure may cause permanent damage to the lungs.

Exposure to wood dust may cause respiratory and skin sensitization.

Carcinogenicity Suspected Cancer Agents of some components used in this product.

(Wood Dust, Formaldehyde)

Mutagenicity No known significant effects or critical hazards.

Teratogenicity No known significant effects or critical hazards.

Developmental effects No known significant effects or critical hazards.

Fertility effects No known significant effects or critical hazards.

Target organs Chronic = Respiratory System, skin. Acute = Skin (cuts, splinters),

Respiratory System, eyes (dust exposure).

Over-exposure signs/symptoms

Inhalation Nasal dryness, coughing, sneezing, sinustis, headache, allergic

reaction, wheezing

Ingestion Not likely, could cause nausea, vomitting, severe abdominal distress.

Skin Splinters can cause infection or allergic skin reaction. Redness,

itching, welts.

Eyes Irritation or damage from dust or splinters.

Medical conditions aggravated by

over-exposure

Asthma

See section 11 for more detailed information on health effects and symptoms.

3. Composition/Information on Ingredients

Chemical NameWt %
Wood, Hardwood and
Not Applicable
5.0 – 8.0

Softwood Mixture

Paper, MDF, Wood, Proprietory Mixture 88.0 – 92.0 Melamine Mixture

PVA Resin, Urea,

Proprietory Mixture 5.0 - 12.0

Adhesive Mixture

Paraffin Wax Emulsion Proprietory Mixture 1.0

4. First Aid Measures

Eye contact Immediately flush eyes with plenty of water for at least 15 minutes,

occasionally lifting the upper and lower eyelids. Check for and remove

any contact lenses. Get medical attention if irritation occurs.

Skin contact Flush contaminated skin with plenty of water. Get medical attention if

symptoms occur.

Inhalation Move exposed person to fresh air. Keep person warm and at rest. If not

breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Get medical attention if symptoms occur.

Ingestion

Wash out mouth with water. Do not induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. Get medical attention if symptoms occur.

Protection of first aid personnel

No action shall be taken involving any personal risk or without suitable

training.

See section 11 for more detailed information on health effects and symptoms.

5. Fire-Fighting Measures

Flash Point Not Determined

Extinguishing media

Suitable Water Spray, Foam, Halon, Carbon Dioxide, Dry Chemical, Any ABC

Class.

Not suitable None known.

Special exposure hazards Promptly isolate the scene by removing all persons from the vicinity of

the incident if there is a fire. No action shall be taken involving any

personal risk or without suitable training.

Explosion sensitivityNot sensitive to static discharge. If dusty conditions develop while

being sanded or manipulated, a sever hazard of an air / dust explosion

may occur.

Special protective equipment for fire-fighters

Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated

in positive pressure mode.

6. Accidental Release Measures

Personal precautions
No action shall be taken involving any personal risk or without suitable

training. Evacuate surrounding areas. Due to the form of this product,

there is no hazrad of release.

Environmental precautions

Waste doors may be disposed of as non-hazardous materials. Dispose of in direct accordance with U.S. Federal, State and local regulations.

7. Handling and Storage

Handling Eating, drinking and smoking should be prohibited in areas where this

material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Do not ingest. Avoid contact with eyes, skin and clothing. Avoid breathing dust generated from this product. Use in well ventilated area or where dust

collection system available.

Storage Keep away from heat, sparks and any other sources of ignition. Do not

> cut or sand doors without adequate dust collection or in unventilated areas. Store only in cool, dry, ventillated area. Appropriate extinguishing equipment must be available in storage area. I.e.

sprinkler system, fire extinguishers.

8. Exposure Controls / Personal Protection

Consult local authorities for acceptable exposure limits.

Recommended monitoring procedures If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment.

Engineering measures

Good general ventilation should be sufficient to control worker exposure to airborne contaminants. If this product contains ingredients with exposure limits, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure below any recommended or statutory limits.

Hygiene measures

Wash hands, forearms and face thoroughly after handling this product, before eating, smoking and using the lavatory and at the end of the working period.

Respiratory

Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

Hands

Leather or other type glove that will protect against cuts and splinters when handling this product.

Eyes

Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to dusts.

Skin

Personal protective equipment for the body should be selected based on the task being performed and the risks involved.

Environmental exposure controls

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, filters or engineering modifications to the process equipment will be necessary to reduce

emissions to acceptable levels.

9. Physical and Chemical Properties

Form Solid pressed wood Flash point Not applicable **Auto-ignition temperature** 400 - 500 degrees F.

Flammable limits

Lower: Not applicable Upper: Not applicable Various Color Odor Slight aromatic рH Not applicable **Boiling point** Not applicable

Freezing Point Not applicable Relative density Not applicable Vapor pressure Not applicable **Odor threshold** Not applicable **Viscosity** Not applicable **Solubility** Not applicable Partition coefficient: n-Not applicable

octanol/water

Evaporation rate Not applicable Vapor density Not applicable

10. Stability and Reactivity

Stability The product is stable.

Conditions to avoid Strong oxidizing agents

Materials to avoid Strong oxidizing agents

Hazardous decomposition Under normal conditions of storage and use, hazardous

products decomposition products should not be produced.

11. Toxicological Information

As manufactured this product poses minimal health hazard. When cut, sanded or manipulated to form dust, inhalation and eye contact may cause irritation. Some types of wood used in this product can cause skin respiratory reactions. Formaldehyde exposure may cause skin and or respiratory sensitization. Suspected Cancer Agents of some components used in this product. (Wood Dust, Formaldehvde)

12. Ecological Information

Environmental effects

No known significant effects or critical hazards.

Other adverse effects

No known significant effects or critical hazards.

13. Disposal Considerations

Waste disposal Waste doors may be disposed of as non-hazardous materials. Dispose

of in direct accordance with U.S. Federal, State and local regulations.

14. Transport Information

The data provided in this section is for information only and may not be specific to your package size or mode of transport. You will need to apply the appropriate regulations to properly classify your shipment for transportation.

International transport regulations

Regulatory UN/NA Proper shipping name Classes/*PG Reportable information number Quantity (RQ)

USDT 49 Non-regulated

CFR

TDG Non-regulated

IMO/IMDG Non-regulated

IATA (Cargo) Non-regulated

15. Regulatory Information

US regulations

HCS Classification Not regulated

U.S. Federal regulations SARA 311/312 Classification Acute – No, Chronic – No, Fire – Yes,

Reactive - No, Sudden Release - No

SARA 302 Extremely Hazardous Substances None required.

State regulations California Prop. 65: None required.

Canada

WHMIS (Canada) Not controlled under WHMIS (Canada).

Canadian NPRI: None required.

International regulations Europe inventory All components are listed or exempted.

Australia inventory (AICS) All components are listed or exempted.

China inventory (IECSC) Not determined. Japan inventory (ENCS) Not determined. Japan inventory (ISHL) Not determined. Korea inventory (KECI) Not determined.

New Zealand Inventory of Chemicals (NZIoC) Not determined.

Philippines inventory (PICCS) Not determined.

Canada inventory All components are listed or exempted.

United States inventory (TSCA 8b) All components are listed or exempted.

16. Other Information

Hazardous Material Information System III

(U.S.A.)

Health: 1 Flammability: 1 Physical hazards: 0

Chronic: 0

Prepared by American Building Supply, Inc.

Date of issue May 1, 2010
Date of printing May 1, 2010
Version 0001

Notice to reader

The information provided herein was believed by American Building Supply ("ABS") to be accurate at the time of preparation or prepared from sources believed to be reliable, but it is the responsibility of the user to investigate and understand other pertinent sources of information, to comply with all laws and procedures applicable to the safe handling and use of the product and to determine the suitability of the product for its intended use. All products supplied by ABS are subject to ABS's terms and conditions of sale. ABS MAKES NO WARRANTY, EXPRESS OR IMPLIED, CONCERNING THE PRODUCT OR THE MERCHANTABILITY OR FITNESS THEREOF FOR ANY PURPOSE OR CONCERNING THE ACCURACY OF ANY INFORMATION PROVIDED BY ABS, except that the product shall conform to ABS's specifications. Nothing contained herein constitutes an offer for the sale of any product.